



RELEASABLE PROFESSIONS • ARTISANS • VERY SMALL BUSINESSES • SHOPS

**1 DOOR
SOLUTION**

**IDEMIA® OPTICAL
SENSOR**

**COMPLIES WITH
CNI USE**



DIGITOUCH® MINI A

PRODUCT INFORMATION SHEET




STANDALONE BIOMETRIC SOLUTION

The DIGITOUCH® MINI A is a new DIGIT MINI EXT biometric reader with SOOTouch® standalone control unit equipped with a 2.8" colour touchscreen interface for controlling the reader and user rights, viewing events, managing an alarm relay and displaying an exit push button.



Ref.:
DIGIT MINI EXT
Dim.:
85X86X56 MM

KEY FEATURES

- ☑ IDEMIA® biometric sensor
- ☑ Infrared finger presence detector
- ☑ Create/Delete users
- ☑ Event display
- ☑ Touch-sensitive push button
- ☑ 2.8" colour touchscreen display
- ☑ Time slots and holidays 
- ☑ Export/restore database
- ☑ Retrieve events 
- ☑ Timer management 
- ☑ Unrestricted access management
- ☑ Intuitive programming
- ☑ Multilingual



Ref.:
SOOTOUCH®
Dim.:
100X88X35 MM
Colour touchscreen dim.:
2.8"



DIGITOUCH® MINI A

TECHNICAL CHARACTERISTICS

FIND TECHNICAL SPECIFICATIONS, INSTALLATION GUIDES AND CONFIGURATION MANUALS AT VAUBAN-SYSTEMS.FR

Ref.: **DIGIT MINI EXT**

Dim.: **85X86X56 MM**










Ref.: **SOOTOUCH®**



Dim.: **100X88X35 MM**

Colour touchscreen dim.: **2.8"**

DIGIT MINI EXT biometric reader

- ▶ 3 LED colours (blue, red, green) for managing door and alarm states 
- ▶ Self-protection against pull-out
- ▶ IDEMIA® optical digital fingerprint sensor with 1-year warranty 
- ▶ Outside reader protection level: IP65 
- ▶ Infrared finger presence detector
- ▶ In-card fingerprint / card only / fingerprint only 
- ▶ Interior - exterior 
- ▶ RS485 connection
- ▶ Moisture resistance of the outside reader: 10% to 80% 
- ▶ Outside reader operating temperature: -10°C to +50°C 
- ▶ Enrolment time less than 5 seconds
- ▶ Identification time less than 1 second
- ▶ Compatible only with MIFARE Classic formats

SOOTOUCH® standalone control unit 1 reader

- ▶ Consumption: 200 mA
- ▶ Supply voltage: 12 VDC
- ▶ Operating temperature: 0°C to 50°C
- ▶ 128 time slots and 32 holiday periods 
- ▶ Push-button entry
- ▶ Wiegand and RS485 protocols
- ▶ 500 users
- ▶ 1 A control relay
- ▶ Alarm control relay
- ▶ Adjustable false acceptance rate
- ▶ USB connection for retrieving events, updating and saving 

OPTIONS AND ACCESSORIES



CASQUETTE MINI

Strongly recommended for outdoor use



Recommended power supply enclosure COFFRET 220 ENCLOSURE



SHEET 